



Series SDL
fluorescent &
HIT downlights



Page 5	SDL 125 vertical fluorescent	125mm Ø 10, 13, 18w
Page 5	SDL 125 Metal Halide	125mm Ø 20, 35, 70w
Page 6	SDL 150 vertical fluorescent	150mm Ø 13, 18, 26, 32w
Page 7	SDL 150 Metal Halide	150mm Ø 35, 70, 150w
Page 8	SDLV 185 vertical fluorescent	185mm Ø 18, 26, 32, 42w
Page 9	SDL 185 Metal Halide	185mm Ø 35, 70, 150w
Page 10	SDL 185 horizontal fluorescent	185mm Ø 13, 2x13, 18, 2x18w
Page 11	SDL 215 sheerline	220mm Ø 2x13, 2x18w, 2x26w
Page 12	SDL 220 horizontal fluorescent	220mm Ø 2x18, 2x26w
Page 13	SDLA 220 asymmetric wall wash	220mm Ø 2x13, 2x18, 2x26w
Page 14	SDL 220 shallow	220mm Ø 2x13, 2x18w
Page 15	SDL 255 horizontal fluorescent	255mm Ø 2x26w, 2x32w
Page 16	SDLA 255 asymmetric wall wash	255mm Ø 2x18, 2x26
Page 17	SDL 255 shallow	255mm Ø 2x26, 2x32, 2x42w
Page 18	SDL 315 horizontal fluorescent	315mm Ø 3x26w
Page 19	Glass options	



Efficient Lighting Systems has combined with Spittler Lichttechnik of Germany to produce a range of high performance, international standard downlights. The German designed and manufactured reflectors are combined with the Australian housing assembly and glass accessories to ensure the products achieve the highest possible quality and competitive prices.

Emphasis has been placed on low glare, visual comfort from the fluorescent downlights. This ensures that even the high performance SDL 315/3x26w offers high illumination levels whilst still providing a low glare, visually pleasing environment.

efficient lighting systems

Spittler Lichttechnik Series SDL downlights



Refer to the SDLS catalogue
for square downlights.



Series SDL Features

- Australian made housing and accessories
- German designed and manufactured reflectors
- Low glare, visual comfort
- 7 reflector sizes from 125mm Ø to 315mm Ø
- Lamp wattages from 1 x 10 Watts to 2 x 42 Watts
- Fully documented photometric data
- Full range of glass lens accessories
- Flexibility to change trim colour or add various attachments at a later date
- Removable die cast aluminium ceiling trim in white and chrome
- All models available with electronic dimming gear

Attachments

All reflectors can be fitted with a range of complimentary attachments (see page 19).



Vandal resistant lens

Available as an additional option.
6mm lens with tamper-proof screws for fluorescent versions only.



High quality German reflectors



Range of glass accessories available

See page 19.



Removable die-cast Aluminium ceiling trim



IP44 rated downlight

Downlights can be optioned with a inlayed G4 or G5 lens sealed into the trim to give an IP44 rating from below the ceiling.



Reflector sizes and types and lamp wattages

Seven reflector sizes and a variety of lamp wattages are available

125mm	Fluorescent Metal Halide Reflector type:	10w, 13w, 18w 20w, 35w, 70w Matt
150mm	Fluorescent Metal Halide Reflector type:	13w, 18w, 26w, 32w 35w, 70w, Matt
185mm	Fluorescent Metal Halide Reflector types:	13w, 18w, 2 x 13w, 2 x 18w, 26w, 32w, 42w 35w, 70w, 150w Metalized Faceted Matt
215mm	Fluorescent Reflector types:	2 x 13w, 2 x 18w, 2 x 26w Metalized
220mm	Fluorescent Reflector types:	2 x 13w, 2 x 18w, 2 x 26w Metalized Cross louvre Faceted Matt Radial
255mm	Fluorescent Reflector types:	2 x 18w, 2 x 26w, 2 x 32w 2 x 42 Metalized Cross louvre Faceted Radial
315mm	Fluorescent Reflector types:	3 x 26w Metalized Cross louvre



DATA AVAILABLE ON CD